



ATTIC CARD

THIS IS GREENFIBER® ALL BORATE LOOSE FILL FORMULA INSULATION

Application Coverage Chart			30 lbs (13.6 kg)			INS765LD	
R-Value at 75° F Mean Temp. Valor de resistencia térmica (valor R) a 75 F de temperatura media	Minimum Thickness (inches) Espesor mínimo (en pulgadas)		Net Coverage (no adjustment for framing) Cubertura neta (sin compensación para la estructura)			Net Coverage (adjusted for 2" x 6" framing on 16" centers) Cubertura neta (con compensación para una estructura de 2" x 6" en centros de 16")	
	Initial Installed Thickness Espesor inicial instalado	Settled Thickness Espesor asentado	Maximum Sq. Ft. per Bag Pies cuadrados máximos por bolsa	Minimum Bags per 1,000 Sq. Ft. Cantidad mínima de bolsas por 1,000 pies cuadrados	Minimum Weight per Sq. Ft. Peso mínimo por pie cuadrado	Maximum Sq. Ft. per Bag Pies cuadrados máximos por bolsa	Minimum Bags per 1,000 Sq. Ft. Cantidad mínima de bolsas por 1,000 pies cuadrados
11	3.36	3.02	100.8	9.9	0.298	111.3	9.0
13	3.99	3.59	83.5	12.0	0.359	92.2	10.8
19	5.86	5.27	54.3	18.4	0.552	59.6	16.8
22	6.77	6.10	45.9	21.8	0.653	49.7	20.1
26	7.99	7.19	37.8	26.4	0.793	40.5	24.7
30	9.19	8.27	32.0	31.2	0.937	33.9	29.5
32	9.79	8.81	29.6	33.7	1.01	31.3	32.0
38	11.57	10.41	24.1	41.4	1.24	25.3	39.6
40	12.16	10.94	22.7	44.1	1.32	23.7	42.2
44	13.33	11.99	20.2	49.6	1.49	21.0	47.6
48	14.49	13.04	18.1	55.2	1.66	18.8	53.2
49	14.78	13.30	17.7	56.6	1.70	18.3	54.6
50	15.07	13.57	17.2	58.1	1.74	17.8	56.1
60	17.96	16.16	13.7	73.1	2.19	14.1	71.0

THE ABOVE COVERAGE CHART IS BASED ON A NOMINAL BAG WEIGHT OF 30 LBS USING A VOLUMATIC III, 3rd GEAR AND 8" GATE. THE CHART IS BASED ON SETTLED THICKNESS AND IS FOR ESTIMATING PURPOSES ONLY. DO NOT EXCEED MAXIMUM SQUARE FEET COVERAGE PER BAG. THE APPLICATOR MUST INSTALL BOTH THE MINIMUM NUMBER OF BAGS PER 1000 SQ. FT. AND THE MINIMUM INSTALLED THICKNESS TO INSURE THE STATED R-VALUE HAS BEEN REACHED. FAILURE TO MEET BOTH THESE REQUIREMENTS MAY PREVENT THE APPLICATION OF SPECIFIED R-VALUE. THIS PRODUCT IS INTENDED FOR DRY APPLICATION ONLY. JOB CONDITIONS, APPLICATION TECHNIQUES, EQUIPMENT, AND SETTING CAN INFLUENCE ACTUAL COVERAGE. DO NOT ADD WATER TO THIS PRODUCT. MINIMUM NET WIEGHT IS 28.5 LBS.

Dry Dense Pack Sidewall Applications (3.5 pcf minimum installed density) 30 lbs. (13.6 kg) INS765LD

Thermal Resistance (R value) Resistencia térmica a (R)	Framing Estructura	Installed Thickness (inches) Espesor instalado (pulgadas)	Minimum Wt. Per Square Foot lb/ft² Peso mínimo por pie cuadrado lb/ft²	Maximum Coverage Per Bag (No Adjustment for Framing) ft²/Bag Cobertura máxima por bolsa (sin compensación para la estructura) ft²/Bag	Maximum Coverage Per Bag (Adjusted for Framing) ft²/Bag Cobertura máxima por bolsa (con compensación para la estructura) ft²/Bag	
					(16" oc)	(24" oc)
13	2x4	3.5	1.02	29.39	32.4	31.3
21	2x6	5.5	1.60	18.70	20.6	19.9

THIS COVERAGE CHART IS FOR DRY APPLICATIONS ONLY AND IS BASED ON THE KREN DL KS200, WITH MATERIAL APPLIED DRY. FOR MAXIMUM COVERAGE PER BAG (ADJUSTED FOR FRAMING), THE FRAMING FACTOR FOR 16" OC STUD SPACING IS 9.375%; FOR 24" OC STUD SPACING THE FRAMING FACTOR IS 6.25%.

GreenFiber provides outstanding thermal performance, fire-resistance and sound control. Consisting of 85% recycled content, GreenFiber Insulation is specially treated for flame resistance.

R-value means resistance to heat flow - the higher the R-value, the greater the insulation power.

CERTIFICATION:

This insulation has been installed in conformance with the above recommendations, to provide a value of R-_____ using _____ bags of this insulation to cover _____ square feet of area.

Builder's Signature: _____
 Company Name: _____
 Date: _____

Applicator's Signature: _____
 Company Name: _____
 Date: _____

FOR MORE INFORMATION CONTACT GREENFIBER:

800.228.0024
greenfiber.info@greenfiber.com

GreenFiber Corporate Office
 2500 Distribution Street, Suite 200
 Charlotte NC 28203
www.greenfiber.com

MANUFACTURING LOCATIONS:

Albany, NY
 Charlotte, NC
 Delphos, OH
 Norfolk, NE
 Phoenix, AZ
 Salt Lake City, UT
 Tampa, FL
 Waco, TX

